



**WACKER
NEUSON**
all it takes!

PS2 500

5000009113

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PS2 500**

PS2 500

Material number 5000009113

Electric, low level residue, single-phase submersible pump for pumping low water levels.



Product details

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Heavy-duty strain relief power cord
- Durable mechanical seals
- Lightweight, compact design

Comes with

- Submersible Pump
- Electrical supply cable
- Operator's manual

Technical specifications

PS2 500

MOTOR	Metric
Nominal current	6,1 A
Nominal speed	3.270 1/min
Nominal voltage	110 V
Nominal frequency	60 Hz
Nominal power	0,480 kW

MECHANICAL - OUTPUT DETAILS	Metric
Flow rate max.	236 l/min
Solid diameter max.	6,0 mm
Delivery height max.	12,0 m

SHIPPING AND STORAGE	Metric
Width for shipping	248 mm
Shipping weight	12,70 kg
Height for shipping	229 mm
Length for shipping	349 mm

ELECTRICAL SYSTEM	Metric
Length Cable	10,00 m

MECHANICAL DETAILS	Metric
Operating weight	9,5 kg
Length	186 mm
Height	304 mm
Width	186 mm

ENVIRONMENT DATA

Metric

Degree of protection

68

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE