



**WACKER  
NEUSON**  
*all it takes!*

## PS2 800

5000620442

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PS2 800**



## PS2 800

Material number 5000620442

Electric, low level residue, single-phase submersible pump for pumping low water levels.

### Product details

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Durable mechanical seals
- Lightweight, compact design

### Comes with

- Submersible Pump
- Electrical supply cable
- Operator's manual

## Technical specifications

### PS2 800

<b>MOTOR</b>	Metric
Nominal current	null, null, 10,1 A
Nominal speed	3.300 1/min
Nominal voltage	null, null, 110 V
Nominal frequency	60 Hz
Nominal power	0,750 kW

<b>SHIPPING AND STORAGE</b>	Metric
Width for shipping	267 mm
Shipping weight	16,36 kg
Height for shipping	260 mm
Length for shipping	475 mm

<b>MECHANICAL - OUTPUT DETAILS</b>	Metric
Flow rate max.	310 l/min
Solid diameter max.	6,0 mm
Delivery height max.	18,0 m

<b>ELECTRICAL SYSTEM</b>	Metric
Cable definition	PVC Sheath
Length Cable	15,00 m
Cable cross-section	2,0 mm <sup>2</sup>

<b>ENVIRONMENT DATA</b>	Metric
Temp. limit borrowed liquid	40 °C
Degree of protection	68

**MECHANICAL DETAILS**

Metric

Operating weight	13,2 kg
Length	192 mm
Intake-/Pressure socket-dia.	50 mm
Height	341 mm
Width	187 mm

**Please Note**

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE