



**WACKER
NEUSON**
all it takes!

PSA2 800

5000620443

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PSA2 800**

PSA2 800

Material number 5000620443

High performance submersible pump to handle solids up to 0.4 in for fast and reliable dewatering.



Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Comes with

- Submersible Pump
- Electrical supply cable
- Operator's manual

Technical specifications

PSA2 800

MOTOR	Metric
Nominal current	null, 5,3 A
Nominal speed	3.300 1/min
Nominal voltage	null, 220 V
Nominal frequency	60 Hz
Nominal power	0,750 kW

SHIPPING AND STORAGE	Metric
Width for shipping	267 mm
Shipping weight	16,96 kg
Height for shipping	260 mm
Length for shipping	475 mm

MECHANICAL - OUTPUT DETAILS	Metric
Flow rate max.	310 l/min
Solid diameter max.	6,0 mm
Delivery height max.	18,0 m

ELECTRICAL SYSTEM	Metric
Cable definition	PVC Sheath
Length Cable	15,00 m
Cable cross-section	2,0 mm ²

ENVIRONMENT DATA	Metric
Temp. limit borrowed liquid	40 °C
Degree of protection	68

MECHANICAL DETAILS

Metric

Operating weight	13,8 kg
Length	192 mm
Intake-/Pressure socket-dia.	50 mm
Height	341 mm
Width	223 mm

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE